

**AL AMEEN GROUP OF COMPANIES**  
 Middle east - Asia - Africa - Europe  
 Post Box No: 92669, Dubai - United Arab Emirates  
 Tel. +971 4 2660 666, +971 4 269 1373, +971 55 19 78 900, + 971 50 903 2003  
 Email. sales@800sign.com , pkmmanaf@gmail.com , abbas@800sign.com  
 www.800sign.com



	43"			49"			55"			65"		
Model No.	KSEAF43	KSEAF43T	KSEAF43C	KSEAF49	KSEAF49T	KSEAF49C	KSEAF55	KSEAF55T	KSEAF55C	KSEAF65	KSEAF65T	KSEAF65C
Display Specifications	non-touch	6 points IR touch	10 points capacitive touch	non-touch	6 points IR touch	10 points capacitive touch	non-touch	6 points IR touch	10 points capacitive touch	non-touch	6 points IR touch	10 points capacitive touch
Unit Price(US\$)	US\$1,180.00	US\$1,260.00	US\$1,800.00	US\$1,260.00	US\$1,530.00	US\$2,160.00	US\$1,440.00	US\$1,700.00	US\$2,320.00	US\$1,980.00	US\$2,200.00	US\$3,000.00

Panel	Panel Type	A grade			A grade			A grade		
	Backlight	LED			LED			LED		
	Backlight Life span	50,000hours			50,000hours			50,000hours		
	Screen Ratio	16:9			16:9			16:9		
	Display Resolution	1920x1080			1920x1080			1920x1080		
	Display Area	943.2(H) mmx 531.4 (V)mm			1073.8(H) mmx 604.0 (V)mm			1209.6(H) mmx 680.4 (V)mm		
	Response Time	≤6ms			≤6ms			≤6ms		
	Color	16.7M color			16.7M color			16.7M color		
	Brightness	≥350 cd/m2			≥350 cd/m2			≥350 cd/m2		
	Contrast ratio	≥3000:1			≥3000:1			≥3000:1		
	Viewing angle	89°(H) / 89°(V)			H178°/V178°			H178°/V178°		
	Operating Temperature	0℃ - 40℃			0℃ - 40℃			0℃ - 40℃		
	Humidity	10-85%			10-85%			10-85%		
	Storage Temperature	-10℃ - 60℃			-10℃ - 60℃			-10℃ - 60℃		

Configuration parameters	Speaker	2X6W(8Ω)			2X6W(8Ω)			2X6W(8Ω)			2X6W(8Ω)		
	Sound Mode	Standard			Standard			Standard			Standard		
	Computer Output Interface	Stereo mini Jack			Stereo mini Jack			Stereo mini Jack			Stereo mini Jack		
	L / R audio output	Audio_L,R_RCA			Audio_L,R_RCA			Audio_L,R_RCA			Audio_L,R_RCA		
	CPU Frequency	quad core 1.6GHz			quad core 1.6GHz			quad core 1.6GHz			quad core 1.6GHz		
	Memory Type	DDR 32G			DDR 32G			DDR 32G			DDR 32G		
	Memory Capacity	8GB			8GB			8GB/16GB(optional)			8GB		
	Multimedia	Video Decoder: FLV,MPEG1/2/4,AVI,WMV,MOV,MP4,TS and etc Image Decoder: JPG/BMP/GIF/TIFF/PNG and etc			Video Decoder: FLV,MPEG1/2/4,AVI,WMV,MOV,MP4,TS and etc Image Decoder: JPG/BMP/GIF/TIFF/PNG and etc			Video Decoder: FLV,MPEG1/2/4,AVI,WMV,MOV,MP4,TS and etc Image Decoder: JPG/BMP/GIF/TIFF/PNG and etc			Video Decoder: FLV,MPEG1/2/4,AVI,WMV,MOV,MP4,TS and etc Image Decoder: JPG/BMP/GIF/TIFF/PNG and etc		
	IO ports	USB 2.0			USB 2.0			USB 2.0			USB 2.0		
	Network	WIFI, RJ45, 4G			WIFI, RJ45, 4G			WIFI, RJ45, 4G			WIFI, RJ45, 4G		

Physical Characteristics	Operating system	Android4.4			Android4.4 / Android5.1			Android4.4			Android4.4		
	Body Dimension (H*W*T)	1745mm*68.5mm*645mm			1740mm*68.5mm*720mm			1892mm*68.5mm*804mm			1930mm*75mm*914mm		
	Base Dimension (H*W*T)	645mm*500mm*55mm			720mm*500mm*55mm			804mm*500mm*55mm			950mm*550mm*70mm		
	Carton Packing Size for Body (L*W*H)	1870mm*195mm*780mm			1910mm*205mm*850mm			2025mm*205mm*940mm			2030mm*175mm*1014mm		
	Carton Packing Size for Base (L*W*H)	730mm*540mm*130mm			800mm*540mm*130mm			890mm*590mm*140mm			1000mm*600mm*125mm		
	Wooden Packing Size for Body (L*W*H)	1900mm*220mm*900mm			1350mm*220mm*980mm			2080mm*250mm*1040mm			2180mm*300mm*1200mm		
	Wooden Packing Size for Base (L*W*H)	660mm*470mm*70mm			830mm*570mm*160mm			900mm*600mm*150mm			1045mm*670mm*140mm		
	N.W	40kg			47kg			68kg			74kg		
G.W	50kg			57kg			78kg			84kg			
Loading Qty	20GP ( pcs)	55pcs			55pcs			36pcs			28pcs		
	40HQ ( pcs)	120pcs			120pcs			90pcs			65pcs		
Frigh Charge	200 \$			200\$			200\$			200\$			

