

AL AMEEN GROUP OF COMPANIES
Middle east - Asia - Africa - Europe
Post Box No: 92669, Dubai - United Arab Emirates
Tel. +971 4 2660 666 , +971 4 269 1373 , +971 55 19 78 900 , + 971 50 903 2003
Email. sales@800sign.com , pkmanaf@gmail.com , abbas@800sign.com
www.800sign.com

		Size			43"			49"			55"			65"
Model No.		KSEWF43	KSEWF43T	KSEWF43C	KSEWF49	KSEWF49T	KSEWF49C	KSEWF55	KSEWF55T	KSEWF55C	KSEWF65	KSEWF65T	KSEWF65C	
Display Specifications		non-touch	6 points IR touch	10 points capacitive touch	non-touch	6 points IR touch	10 points capacitive touch	non-touch	6 points IR touch	10 points capacitive touch	non-touch	6 points IR touch	10 points capacitive touch	
Unit Price(US\$)		US\$1,640.00	US\$1,800.00	US\$2,400.00		US\$1,980.00	US\$2,600.00	US\$1,980.00	US\$2,200.00	US\$2,800.00	US\$2,200.00	US\$2,520.00	US\$3,200.00	
Panel	Panel Type	A grade			A grade			A grade			A grade			
	Backlight	LED			LED			LED			LED			
	Backlight Life span	60,000hours			60,000hours			60,000hours			60,000hours			
	Screen Ratio	16:9			16:9			16:9			16:9			
	Display Resolution	1920x1080			1920x1080			1920x1080			1920x1080			
	Display Area	943.2(H) mmx 531.4 (V)mm			1073.8(H) mmx 604.0 (V)mm			1209.6(H) mmx 680.4 (V)mm			1428.48(H) mmx803.52 (V)mm			
	Response Time	≤6ms			≤6ms			≤6ms			≤6ms			
	Color	16.7M color			16.7M color			16.7M color			16.7M color			
	Brightness	≥350 cd/m2			≥350 cd/m2			≥350 cd/m2			≥350 cd/m2			
	Contrast ratio	≥1200:1			≥1200:1			≥1200:1			≥5000:1			
	Viewing angle	89°(H) / 89°(V)			H178°/V178°			H178°/V178°			H178°/V178°			
	Operating Temperature	0℃ - 40℃			0℃ - 40℃			0℃ - 40℃			0℃ - 40℃			
	Humidity	10-85%			10-85%			10-85%			10-85%			
	Storage Temperature	-10℃ - 60℃			-10℃ - 60℃			-10℃ - 60℃			-10℃ - 60℃			
Power Input	AC100 - 240V-(+/- 10 %) 50/60Hz			AC100 - 240V-(+/- 10 %) 50/60Hz			AC100 - 240V-(+/- 10 %) 50/60Hz			AC100 - 240V-(+/- 10 %) 50/60Hz				
Power consumption	≤100W			≤160W			≤160W			≤160W				
Standby power consumption	< 0.5W			< 0.5W			< 0.5W			< 0.5W				
Built-in PC technical specification (Optional)														
Audio system	Output interface	Speaker	2X6W(8Ω)											
		Sound model	Standard											
		PC output interface	HDMI*1/VGA*1/RJ45*1/USB*4/WIFI*1											
		L/R audio output	1 RCA X2											
	CPU	Intel Core i3/i5/i7												
	CPU Frame	≈1.8GHz												
	CPU Interface	On board CPU												
	Memory type	DDR3												
	Memory	4GB/8G												
	HD type	SATA III												
	HD capacity	500G HD /120G SSD/256G SSD												
	Wireless NIC	Mini PCI port												
OS	Windows 7/Windows 8(Cloner version just for testing)													
Physical Characteristics	Body Dimension (H*W*T)	1745mm*68.5mm*645mm	1740mm*68.5mm*720mm	1892mm*68.5mm*804mm	1930mm*75mm*914mm									
	Base Dimension (H*W*T)	645mm*500mm*55mm	720mm*500mm*55mm	804mm*500mm*55mm	950mm*550mm*70mm									
	Carton Packing Size for Body (L*W*H)	1870mm*195mm*780mm	1910mm*205mm*850mm	2025mm*205mm*940mm	2030mm*175mm*1014mm									
	Carton Packing Size for Base (L*W*H)	730mm*540mm*130mm	800mm*540mm*130mm	890mm*590mm*140mm	1000mm*600mm*125mm									
	Wooden Packing Size for Body (L*W*H)	1900mm*220mm*900mm	1920mm*220mm*980mm	2080mm*250mm*1040mm	2180mm*300mm*1200mm									
	Wooden Packing Size for Base (L*W*H)	660mm*470mm*70mm	830mm*570mm*160mm	900mm*600mm*150mm	1045mm*670mm*140mm									
	N.W	40kg	46kg	68kg	74kg									
G.W	79kg	112kg	113kg	139kg										
Loading Qty	20GP (pcs)	55pcs	55pcs	36pcs	28pcs									
	40HQ (pcs)	120pcs	120pcs	90pcs	65pcs									
Fright Charge	200 \$	200\$	200\$	200\$										
Picture														